

CLAIMS

1. A voltage and/or surge-current protector and grounding bar arrangement for use with a BIX connector block, comprising in combination:

5 a BIX connector block having two rows of terminals which are laterally spaced apart with respect to each other so as to form a longitudinally extending channel therebetween;

a grounding bar disposed within said longitudinally extending channel defined between said two laterally spaced rows of terminals and having a plurality of holes defined therein;

a housing;

voltage and/or surge-current protector means disposed within said housing;

15 a plurality of tip/ring terminal contacts disposed within said housing for mating with opposed terminals of said BIX connector block, disposed upon opposite sides of said longitudinally extending channel, when said housing is mounted upon said BIX connector block; and

20

ground contact means disposed within said housing for connection to said voltage and surge-current protector means and to one of said plurality of holes defined within said grounding bar.

2. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 1, wherein said housing includes a pair of co-mating front and back halves.

3. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 1, wherein said voltage and/or surge-current protector means comprises a pair of voltage suppressor means and a pair of sneak-current fuses so as to provide over-voltage and over-current protection for said BIX connector block.

4. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 1, wherein said voltage and/or surge-current protector means comprises rectifying means, a pair of voltage suppressor means, and a pair of sneak-current fuses so as to provide over-voltage and over-current protection for said BIX connector block.

5. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 1, wherein said voltage and/or surge-

current protector means comprises a pair of voltage suppressor means so as to provide over-voltage protection for said BIX connector block.

6. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 1, wherein said voltage and/or surge-current protector means comprises a pair of sneak-current fuses so as to provide over-current protection for said BIX connector block

7. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 3, wherein said pair of voltage suppressor means comprises a pair of silicon avalanche suppressors.

8. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 4, wherein said rectifying means comprises a diode bridge rectifier and said pair of voltage suppressor means comprises a pair of silicon avalanche suppressors.

9. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 1, further comprising disconnect means disposed within said housing for allowing testing and line-servicing without removal of said voltage and/or surge current protector means
5 from said BIX connector block.

10. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 9, wherein said disconnect means comprises a long disconnect terminal contact, a short disconnect terminal contact, and a spring contact, said spring contact urging
5 said short disconnect terminal contact into contact engagement with said long disconnect terminal contact when no testing is being performed.

11. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 1, wherein an upper portion of said housing has a test port for receiving therein a test probe for permitting testing.

12. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 1, wherein an upper portion of said housing has a recess for receiving therein a label strip so as to allow for single pair identification of up to 25 terminal-pairs which
5 is visible without removal of said voltage and/or surge-current protector means from said BIX connector block.

20140909 10:44:09

13. A voltage and/or surge-current protector and grounding bar arrangement for use with a BIX connector block, comprising in combination:

5 a BIX connector block having two rows of terminals which are laterally spaced apart with respect to each other so as to form a longitudinally extending channel therebetween;

grounding bar means disposed within said longitudinally extending channel defined between said two laterally spaced rows of terminals and having a plurality of holes defined therein;

a housing;

voltage and/or surge-current protector means disposed within said housing;

15 a plurality of tip/ring terminal contacts disposed within said housing for mating with opposed terminals of said BIX connector block, disposed upon opposite sides of said longitudinally extending channel, when said housing is mounted upon said BIX connector block;

20 ground contact means disposed within said housing for connection to said voltage and surge-current protector

means and to one of said plurality of holes defined within
said grounding bar means; and

25 disconnect means disposed within said housing for
allowing testing and line-servicing without removal of said
voltage and/or surge-current protector means from said BIX
connector block.

14. A voltage and/or surge-current protector and grounding bar
arrangement as claimed in Claim 13, wherein said disconnect means
comprises a long disconnect terminal contact, a short disconnect
terminal contact, and a spring contact, said spring contact urging
said short disconnect terminal contact into contact engagement with
said long disconnect terminal contact when no testing is being
performed.

15. A voltage and/or surge-current protector and grounding bar
arrangement as claimed in Claim 13, wherein an upper portion of said
housing has a test port for receiving therein a test probe for permit-
ting testing.

16. A voltage and/or surge-current protector and grounding bar
arrangement as claimed in Claim 13, wherein an upper portion of said
housing has a recess for receiving therein a label strip so as to

allow for single pair identification of up to 25 terminal-pairs which
5 is visible without removal of said voltage and/or surge-current pro-
tector means from said BIX connector block.

5
10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500

17. A voltage and/or surge-current protector and grounding bar
arrangement as claimed in Claim 13, wherein said voltage and/or surge-
current protector means comprises a pair of voltage suppressor means
and a pair of sneak-current fuses so as to provide over-voltage and
5 over-current protection for said BIX connector block.

18. A voltage and/or surge-current protector and grounding bar
arrangement as claimed in Claim 13, wherein said voltage and/or surge-
current protector means comprises rectifying means, a pair of voltage
suppressor means, and a pair of sneak-current fuses so as to provide
5 over-voltage and over-current protection for said BIX connector block.

19. A voltage and/or surge-current protector and grounding bar arrangement for use with a BIX connector block, comprising:

5 a BIX connector block having two rows of terminals which are laterally spaced apart with respect to each other so as to form a longitudinally extending channel there-between;

10 a grounding bar including an elongated flat horizontal intermediate section and a pair of terminal end sections integrally connected to the opposite ends of said intermediate section;

15 said grounding bar being disposed within said longitudinally extending channel defined between said two laterally spaced rows of terminals, said two laterally spaced rows of terminals in said intermediate section having a plurality of holes defined therein; and

protuberances located at ends of said BIX connector block for receiving therein corresponding vertical offsets on said terminal end portions of said grounding bar.

20. A voltage and/or surge-current protector and grounding bar arrangement as claimed in Claim 19, wherein rectangularly-shaped apertures formed above and below said vertical offset through which

said protuberances extend for fixedly securing said grounding bar
5 within said longitudinally extending channel.

2025-04-04 10:44:04